



EUTECTIC PLATES & FREEZER

- Long life 2 years
- Safe to be touched
- Solid, Clean, Clear, Reusable
- Environmental & User friendly
- Plastic pack made of Polyethylene (PE Food Grade)
- Always have 2 sets: One in use and the other being refrozen, thus ready for immediate use



Models	Dimensions (mm)			Weight (kg)	Temperatures (dC)
	Length	Width	Thickness		
DEP-0.5	207	80	35	0.5	-3, -10, -15, -21, -26, -28, -30
DEP-2.2	300	203	30	2.2	
DEP-3.0	410	200	37	3	
DEP-5.0	410	305	37	5	

- Insulation thickness of 80 mm. low power consumption and condensation on outer tank
- Double layers rubber seal, special elasticity property for low temperature
- Door handle "built in pressure relieve system" stronger and comfortable
- Fan motor support design: less noise emission, better heat rejection



Model:	DEF-90L	DEF-160L	
<i>Number of Shelves</i>	10,12	20,22	Shelves
<i>Eutectic tray Dimension</i>	650x475	650x476	mm
<i>Number of 0.5/2.2/5.0 kg Pack in 1 Shelf</i>	17/4/2	17/4/3	packs
<i>Gross capacity</i>	300	522	Liters
<i>Freezing Capacity at +40dC</i>	395	720	Watt
	75-80	160-180	Kg of Plate
<i>Full load freezing time</i>	12-22	12-22	Hours
<i>Range of inside temperature</i>	-15 to -45	-15 to -45	dC
<i>Lenght x Depth x Height</i>	670x870x1470	670x871x2030	mm
<i>Weight</i>	160-170	240-250	Kg
<i>Insulation Thickness</i>	80	80	mm
<i>Refrigerant</i>	R 507	R 507	
<i>Connecting Power</i>	650	1300	Watt
<i>Input Current (maximum)</i>	3.75	6.8	Amp
<i>Fusing</i>	15	15	Amp
<i>Power Consumption</i>	12-14.4	20-24.5	Kwh/24Hrs

DEXTRA INDUSTRY AND TRANSPORT

5th floor, Lumpini II Building, 247 Sarasin Road, Lumpini Pathumwan,

Bangkok 10330, THAILAND

Tel: (+662) 651 9027-36 Fax: (+662) 651 8005-6

E-mail contact: coldchain@dextragroup.com

Contact name : Jean Balsemin